


Swivel modules DSM/DSM-B

FESTO




Key features

At a glance


- Double-acting semi-rotary drive with vane
- The swivel angle is infinitely adjustable over the entire swivel range
- High precision thanks to fixed metal stops
- Polyurethane ensures a long service life for the rotary vane and sealing system
- Easy precision adjustment of the end positions using the cushioning components
- The mechanical gearing between the stop element and the semi-rotary drive prevents movement of the stop system under load
- Torques of up to 80 Nm with tandem rotary vanes in combination with multi-tooth shaft

The technology in detail

Size 6 ... 10



Size 12 ... 63




- [1] Interface
Choice of:
 - Spigot shaft
 - Flanged shaft
- [2] Wide range of mounting options
- [3] Cushioning with size 6 ... 10: elastic cushioning elements with metal fixed stop (P)
Cushioning with size 12 ... 63:
Three cushioning types, with metal fixed stop:
 - Elastic cushioning components (P)
 - Adjustable, elastic cushioning elements (P1)
 - Hydraulic shock absorbers (CC)
- [4] Position sensing
 - With size 6 ... 10: SME/SMT-10
 - With size 12 ... 40: SME/SMT-10 or SIEN
 - For size 63: SME/SMT-8
- [5] Precision adjustment of the end positions: the end positions can be very accurately adjusted by moving the stops
- [6] Angle scale: the required swivel angle can be easily preset using the scale
- [7] The cover cap prevents unwanted interference in the swivel motion and reduces the risk of injury

Key features

Wide choice of variants

DSM-T-...: semi-rotary drive with tandem rotary vanes



Torques of up to 80 Nm can be achieved by having two rotary vanes on the multi-tooth shaft.

The functionality is the same as that of the DSM without tandem rotary vanes:

- Infinitely adjustable swivel angle
- Identical interfaces
- Identical accessories

DSM-...-HD: : semi-rotary drive with heavy-duty bearing



High-quality bearing elements with backlash-free preloading enable very high load torques and an extremely precise bearing with excellent running accuracy. The functionality corresponds to that of the DSM-B without heavy-duty bearing:

- Infinitely adjustable swivel angle
- Identical mounting interfaces
- Identical accessories






Choice of two cushioning types:

- Cushioning P1 and CC

Product range overview

Characteristic values of the semi-rotary drives






The specifications shown in the table are maximum values. The exact values for the individual sizes can be found on the following pages.

Version	Type	Size	Swivel angle [°]	Torque [Nm]	Axial force [N]	Radial force [N]
Spigot shaft						
	DSM-...	6, 8, 10	90, 180	0.85	10	30
		10	240			
		12, 16, 25, 32, 40, 63	270	40	500	500
		12, 16, 25, 32	246			
		40, 63	240			
Flanged shaft						
	DSM-...-FW	6, 8, 10	90, 180	0.85	10	30
		10	240			
		12, 16, 25, 32, 40, 63	270	40	500	500
		12, 16, 25, 32	246			
		40, 63	240			
Tandem rotary vanes and spigot shaft						
	DSM-T-...	6, 8, 10	90, 180	1.7	10	30
		10	240			
		12, 16, 25, 32, 40, 63	270	80	500	500
		12, 16, 25, 32	246			
		40, 63	240			
Tandem rotary vanes and flange shaft						
	DSM-T-...-FW	6, 8, 10	90, 180	1.7	10	30
		10	240			
		12, 16, 25, 32, 40, 63	270	80	500	500
		12, 16, 25, 32	246			
		40, 63	240			
Heavy-duty bearing						
	DSM-...-HD	12, 16, 25, 32, 40, 63	270	40	1 300	1 800
		12, 16, 25, 32	246			
		40, 63	240			

Product range overview

Characteristic values of the semi-rotary drives

The specifications shown in the table are maximum values. The exact values for the individual sizes can be found on the following pages.

Version	Cushioning			Adjustable swivel angle	Position sensing	→ Page
	P	P1	CC		A	
Spigot shaft						
	■	—	—	■	■	8
	■	—	—	■	■	
	■	—	—	■	■	24
	—	■	■	■	■	
	—	■	■	■	■	
Flanged shaft						
	■	—	—	■	■	8
	■	—	—	■	■	
	■	—	—	■	■	24
	—	■	■	■	■	
	—	■	■	■	■	
Tandem rotary vanes and spigot shaft						
	■	—	—	■ ²⁾	■ ³⁾	8
	■	—	—	■ ²⁾	■ ³⁾	
	■	—	—	■	■	24
	—	■ ¹⁾	■	■	■	
	—	■ ¹⁾	■	■	■	
Tandem rotary vanes and flange shaft						
	■	—	—	■ ²⁾	■ ³⁾	8
	■	—	—	■ ²⁾	■ ³⁾	
	■	—	—	■	■	24
	—	■ ¹⁾	■	■	■	
	—	■ ¹⁾	■	■	■	
Heavy-duty bearing						
	—	—	—	■	■	24
	—	■	■	■	■	
	—	■	■	■	■	

1) The cushioning type P1 can be ordered as an accessory (→ page 53).

2) The stop kit (adjustable swivel angle) can be ordered as an accessory (→ page 54).


3) The mounting kit (for position sensing) can be ordered as an accessory (→ page 54).

Key features


Mounting options

Size 6 ... 10


Via threaded through-hole/through-hole



Via through-hole, lateral




Via thread, lateral




Size 12 ... 63


Via threaded through-hole




Via through-hole



Via thread, lateral




Centring via centring collar




Special mounting options for DSM-...-HD

Via thread, lateral



Of attachments



Positive-locking connections possible through use of centring sleeves ZBH.




Key features

Accessories

Free wheel unit FLSM
Size 6 ... 40

Push-on flange FWSR
Size 6 ... 40

Mounting plate HSM
Size 12 ... 40




Direction of rotation in combination with freewheel unit FLSM


The freewheel unit only allows movement in one of the two possible swivel directions of the swivel module DSM. The reverse direction is blocked.

Dimensions and ordering data
→ page 49

FLSM-...-R, clockwise rotation



FLSM-...-L, anti-clockwise rotation



[1] View towards drive shaft

Position sensor SRBS

The position sensor is used for sensing the end positions of the swivel module DSM.


Sensing is magnetic and contactless. Two switching points are output.

Key features:

- Quick assembly without having to manually search for switching points
- Simple and reliable operation using one pushbutton
- Only one connecting cable required
- Long service life thanks to sturdy and non-contacting position sensing

Technical data:

- Possible sensing range: 0 ... 270°
- Repetition accuracy: $\leq 1^\circ$
- 2 switching outputs (24 V)
- Switching output: PNP or NPN, programmable
- Switching element function: N/O contact or N/C contact programmable




Type codes DSM-6 ... 10

001	Series
DSM	Semi-rotary drive
002	Design type
	Standard
T	Tandem vane
003	Size
6	6
8	8
10	10
004	Nominal swivel angle [°]
90	90
180	180
200	200
240	240

005	Cushioning
P	Elastic cushioning rings/plates on both sides
006	Position sensing
	None
A	For proximity sensor
007	Adjustable swivel angle
	Fixed swivel angle
FF	Adjustable swivel angle
008	Shaft
	Spigot shaft
FW	Flanged shaft

Peripherals overview DSM-6 ... 10




Peripherals overview DSM-6 ... 10


Accessories		Description	→ Page/Internet
[1]	Quarter turn actuator DSM	Drives with rotary vanes	10
[2]	Push-on flange FWSR	For retrofitting on swivel module DSM with spigot shaft	51
[3]	Freewheel unit FLSM	- For synchronised rotary movement in one direction - Only in combination with swivel module DSM with spigot shaft	49
[4]	One-way flow control valve GRLA	For regulating speed	57
[5]	Push-in fitting QS	For connecting tubing with standard O.D.	qs
[6]	Stop kit KSM	- For adjusting the swivel angle - Can be retrofitted for semi-rotary drive DSM-...-P(-A)/DSM-...-P(-A)-FW - With DSM-T..., the stop kit must be ordered separately as an accessory - Can be combined with mounting kit WSM - The adapter kit DADP-AK must also be ordered in combination with mounting kit WSM → page 54	54
[7]	Adapter kit DADP-AK	For attaching mounting kit WSM to stop kit KSM	54
[8]	Mounting kit WSM-...-SME-10	- For sensing the swivel angle - For mounting the proximity switch SME-/SMT-10; - Can be retrofitted for semi-rotary drive DSM-...-P(-FF)/DSM-...-P(-FF)-FW - The mounting kit must be ordered as an accessory with DSM-T... - Can be combined with stop kit KSM - The adapter kit DADP-AK must also be ordered in combination with stop kit KSM → page 54	54
[9]	Proximity switch SME/SMT-10	Proximity switches for sensing the end position	54
[10]	Position sensor SRBS	- For sensing the swivel angle - No adjustment of the proximity switches required - The end positions of the swivel angle are taught in at the touch of a button - Can only be mounted directly on the semi-rotary drive, without other accessories - Must be ordered separately as an accessory	53

Datasheet DSM-6 ... 10

Function



Size
6 ... 10



General technical data				
Size	6	8	10	
Pneumatic connection	M3			
Design	Vane			
Cushioning	Elastic cushioning rings/plates at both ends			
Type of mounting	With female thread			
Mounting position	Any			
Swivel angle				
DSM-... [°]	90 or 180	90 or 180	90, 180 or 240	
DSM-...-FF [°]	0 ... 180		0 ... 200	
Max. swivel frequency at 6 bar [Hz]	3		3 (at 240°: 2 Hz)	
Cushioning angle [°]	0.5			
Air consumption at swivel angle of 90° and 6 bar ¹⁾				
DSM-... [cm ³]	0.6	0.7	5.5	
DSM-T-... [cm ³]	1.2	1.4	11	

1) Theoretical values

Operating and environmental conditions				
Size	6	8	10	
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]			
Operating pressure				
DSM-... [bar]	3.5 ... 8	3.5 ... 8	2.5 ... 8	
DSM-T-... [bar]	4 ... 8	4 ... 8	3.5 ... 8	
Ambient temperature ¹⁾ [°C]	0 ... +60			
Storage temperature [°C]	20			
ATEX	Selected types → www.festo.com			
CE marking (see declaration of conformity)	To EU Explosion Protection Directive (ATEX)			
UKCA marking (see declaration of conformity)	To UK explosion regulations			
Explosion protection certification outside the EU	EPL Gb (GB)			
	EPL Db (GB)			

1) Note operating range of proximity switches

Forces and torques				
Size	6	8	10	
Torque at 6 bar				
DSM-... [Nm]	0.15	0.35	0.85	
DSM-T-... [Nm]	0.3	0.7	1.7	
Max. permissible axial force on drive shaft ¹⁾ [N]	10			
Max. permissible radial force on drive shaft ¹⁾ [N]	15	20	30	
Max. permissible mass moment of inertia on drive shaft ²⁾ [kgm ²]	0.00065	0.0013	0.0026	

1) The axis of rotation and the centre of the drive shaft are the point of reference for the forces

2) Maximum value; please see graphs starting on → page 12


2) Maximum value; please see graphs starting on → page 12

Datasheet DSM-6 ... 10


Weight [g]			
Size	6	8	10
Spigot shaft			
DSM-...-P	45	78	140
DSM-...-P-A	50	85	149
DSM-...-P-FF	70	140	240
DSM-...-P-A-FF	85	155	255
Flanged shaft			
DSM-...-P-FW	51	85	150
DSM-...-P-A-FW	56	92	159
DSM-...-P-FF-FW	76	147	250
DSM-...-P-A-FF-FW	91	162	265
Tandem rotary vanes and spigot shaft			
DSM-T-...-P	60	110	200
Tandem rotary vanes and flange shaft			
DSM-T-...-P-FW	65	117	210

Materials


Sectional view
with spigot shaft
DSM-...




DSM-T-...



with flange shaft
DSM-...-FW



DSM-T-...-FW



Semi-rotary drive



[1]	Shaft	High-alloy stainless steel
[2]	Vane	Glass fibre-reinforced plastic
[3]	Housing	Anodised aluminium
–	Screws	Galvanised steel
	Seals	Polyurethane
	Note on materials	RoHS-compliant
	LABS (PWIS) conformity	VDMA24364-B1/B2-L

Datasheet DSM-6 ... 10


Mass moment of inertia J as a function of swivel time t

DSM-6

DSM-8



DSM-10




Datasheet DSM-6 ... 10

Dimensions


Download CAD data → www.festo.com

DSM-... – With spigot shaft



For DSM-10

Shaft position


Note

For swivel angle tolerance → table below. The compressed air supply ports are at the bottom in this drawing.

Size	B1	B2	B3	B4	D1 ø g7	D2 ø	D3 ø f8	D4 ø H12	D5	D6	D7 ø H12	D8 ø	D9 ø H12	D10	EE
6	10	25	30	17	4	8	14	3.2	M3	M2	40	29.4	3.5	M2	M3
8	12.8	31	38	20	5	9	16	3.2	M3	M2.5	50	37.4	3.5	M2	M3
10	15.9	38	47	26	6	12	19	4.3	M4	M3	62	46.4	4.5	M2.5	M3


Size	L1	L2	L3	L4	L5	L6	L7	L8	L9	T1	T2 h12	≅	Swivel angle tolerance
6	43	13	10	2	9.8	21	5	6	3	3.5	4	3	0/+5°
8	50	16	13	2	11.3	23	6	6.5	3	4.5	4.3	3.5	0/+5°
10	61	19.6	16	2	14.3	28.4	8	7.5	4	–	5	4.5	0/+5°

Datasheet DSM-6 ... 10

Dimensions


Download CAD data → www.festo.com

DSM-T... – With spigot shaft and tandem rotary vanes



For DSM-T-10

Shaft position



 **Note**

For swivel angle tolerance → table below. The compressed air supply ports are at the bottom in this drawing.

Size	B1	B2	B3	B4	D1 ø g7	D2 ø	D3 ø f8	D4 ø H12	D5	D6	D7 ø H12	D8 ø	D9 ø H12	D10
6	10	25	30	17	4	8	14	3.2	M3	M2	40	29.4	3.5	M2
8	12.8	31	38	20	5	9	16	3.2	M3	M2.5	50	37.4	3.5	M2
10	15.9	38	47	26	6	12	19	4.3	M4	M3	62	46.4	4.5	M2.5

Size	EE	L1	L2	L3	L4	L5	L6	L7	L8	L9	T1	T2 h12	⌀	Swivel angle tolerance
6	M3	55.5	13	10	2	9.8	33.5	5	6	3	3.5	4	3	0/+5°
8	M3	64.5	16	13	2	11.3	37.5	6	6.5	3	4.5	4.3	3.5	0/+5°
10	M3	79	19.6	16	2	14.3	46	8	7.5	4	–	5	4.5	0/+5°


Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-... – With spigot shaft and position sensing

DSM-T-... – With spigot shaft, tandem rotary vanes and position sensing



[1] Proximity switch not included in the scope of delivery. Observe fitting space for proximity switch and cable guide

[2] Position of the magnet

[3] Max. tightening torque for sensor bracket screws
→ table below

[4] The flat or the featherkey on the shaft indicates the position of the rotary vane

Size	D8 ø	D9 ø	L3	L4	L5	L6		L7	Tightening torque [Nm]
						DSM-...	DSM-T-...		
6	29.4	17.3	4	2	9.8	21	33.5	19.5	0.19
8	37.4	19.3	4	2	11.3	23	37.5	19.5	0.32
10	46.4	22.3	4	2	14.3	28	45.6	19.5	0.44


Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-... – With spigot shaft and adjustable swivel angle

DSM-T-... – With spigot shaft, tandem rotary vanes and adjustable swivel angle



 **Note**

The swivel angle is infinitely adjustable over the entire swivel range. Size 6 mm can only be adjusted symmetrically around the centre position.

- [1] Supply ports
- [2] Locking screw for clamping the stop
- [3] End-position adjustment
- [4] Lock nut for end-position adjustment
- [5] Infinitely adjustable stops

Size	B1	B2	B3	B4	D1 ø g7	D2 ø f8	D3 ø H12	D4 ø H12	D5	D6	D7 ø H12	D8 ø H12	D9 ø H12	D18 ø H12	EE	L1	
																DSM-...	DSM-T-...
6	10	25	30	17	4	8	14	3.2	M3	M2	40	29.4	3.5	22	M3	52	64.5
8	12.8	31	38	20	5	9	16	3.2	M3	M2.5	50	37.4	3.5	26	M3	64	78.5
10	15.9	38	47	26	6	12	19	4.3	M4	M3	62	46.4	4.5	35.8	M3	76	93.6

Size	L2	L3	L4	L5	L6		L7	L8	L9	T1	≈G	Max. swivel angle	Precision adjustment per side
					DSM-...	DSM-T-...							
6	13	10	2	9.8	21	33.5	17.8	6	3	3.5	4	180°+5°	+1°/-5°
8	16	13	2	11.3	23	37.5	24.9	6.5	3	4.5	5	180°+5°	+1°/-5°
10	19.6	16	2	14.3	28.4	46	28.2	7.5	4	–	5.5	200°+5°	+1°/-5°


Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-... – With spigot shaft, adjustable swivel angle and position sensing

DSM-T-... – With spigot shaft, tandem rotary vanes, adjustable swivel angle and position sensing



[1] Sensor not included in the scope of delivery. Observe fitting space for proximity switch and cable guide

[2] Position of the magnet

[3] Max. tightening torque for sensor bracket screw
→ table below

[4] The flat or the featherkey on the shaft indicates the position of the rotary vane


Size	D8 Ø	D9	L1		L3	L4	L5	L6		L7	Tightening torque [Nm]
			DSM-...	DSM-T-...				DSM-...	DSM-T-...		
6	29.4	17.3	68.5	81	4	2	9.8	21	33.5	19.5	0.19
8	37.4	19.3	80	94.5	4	2	11.3	23	37.5	19.5	0.32
10	46.4	22.3	91.5	109.1	4	2	14.3	28.4	46	19.5	0.44

Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-... – With flange shaft



Size	B1	B2	B3	B4	D1 ø	D2 ø g7	D3 ø f8	D4 ø	D5	D6	D7 ø H12	D8 ø	D9 ø H12	D10 ø	D11	D12 ø H13	D13 ø
6	10	25	30	17	8	8	14	3.2	M3	M2	40	29.4	3.5	23	M3	3.4	16
8	12.8	31	38	20	9	11	16	3.2	M3	M2.5	50	37.4	3.5	27	M3	3.4	21
10	15.9	38	47	26	10	11	19	4.3	M4	M3	62	46.4	4.5	30	M3	3.4	21


Size	D14	EE	L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	T1	≡	Swivel angle tolerance
6	M2	M3	39.5	30	7.5	2	9.8	21	5	6	3	3	1.5	4	3	0/+5°
8	M2	M3	43.5	34	7.5	2	11.3	23	6	6.5	3	3	1.5	4.3	3.5	0/+5°
10	M2.5	M3	53	41.4	9.6	2	14.3	28.4	8	7.5	4	3	1.6	5	4.5	0/+5°

Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-T... – With flange shaft and tandem rotary vanes



Size	B1	B2	B3	B4	D1 ø	D2 ø g7	D3 ø f8	D4 ø	D5	D6	D7 ø H12	D8 ø	D9 ø H12	D10 ø	D11	D12 ø H13	D13 ø
6	10	25	30	17	8	8	14	3.2	M3	M2	40	29.4	3.5	23	M3	3.4	16
8	12.8	31	38	20	9	11	16	3.2	M3	M2.5	50	37.4	3.5	27	M3	3.4	21
10	15.9	38	47	26	10	11	19	4.3	M4	M3	62	46.4	4.5	30	M3	3.4	21

Size	D14	EE	L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	T1	≙	Swivel angle tolerance
6	M2	M3	52	42.5	7.5	2	9.8	33.5	5	6	3	3	1.5	4	3	0/+5°
8	M2	M3	58	48.5	7.5	2	11.3	37.5	6	6.5	3	3	1.5	4.3	3.5	0/+5°
10	M2.5	M3	71	59.4	9.6	2	14.3	46	8	7.5	4	3	1.6	5	4.5	0/+5°


Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-... – With flange shaft and position sensing

DSM-T-... – With flange shaft, tandem rotary vanes and position sensing



[1] Proximity switch not included in the scope of delivery. Observe fitting space for proximity switch and cable guide


[2] Position of the magnet

[3] Max. tightening torque for sensor bracket screw → table below

Size	D8 ø	D9 ø	L1		L3	L4	L5	L6		L7	Tightening torque [Nm]
			DSM-...	DSM-T-...				DSM-...	DSM-T-...		
6	29.4	17.3	50	62.5	4	2	9.8	21	33.5	19.5	0.19
8	37.4	19.3	52	66.5	4	2	11.3	23	37.5	19.5	0.32
10	46.4	22.3	59.5	77.1	4	2	14.3	28.4	46	19.5	0.44

DSM-... – With flange shaft and adjustable swivel angle

DSM-T-... – With flange shaft, tandem rotary vanes and adjustable swivel angle



Without orifice and covering

Note

The swivel angle is infinitely adjustable over the entire swivel range.
Size 6 mm can only be adjusted symmetrically around the centre position.

- [1] Supply ports
- [2] Locking screw for clamping the stop
- [3] End-position adjustment
- [4] Lock nut for end-position adjustment
- [5] Infinitely adjustable stops

Size	B1	B2	B3	B4	D1 ø	D2 ø g7	D3 ø f8	D4 ø H12	D5	D6	D7 ø H12	D8 ø	D9 ø H12	D10 ø	D11	D12 ø H13	D13 ø	D18 ø	EE
6	10	25	30	17	8	8	14	3.2	M3	M2	40	29.4	3.5	23	M3	3.4	16	22	M3
8	12.8	31	38	20	9	11	16	3.2	M3	M2.5	50	37.4	3.5	27	M3	3.4	21	26	M3
10	15.9	38	47	26	10	11	19	4.3	M4	M3	62	46.4	4.5	30	M3	3.4	21	35.8	M3

Size	L1		L2	L3	L4	L5	L6		L7	L8	L9	L10	L11	≙	Max. Swivel angle	Precision adjustment per side
	DSM-...	DSM-T-...					DSM-...	DSM-T-...								
6	48	60.5	9.5	8	2	9.8	21	33.5	17.8	6	3	3	1.5	4	180° +5°	+1°/-5°
8	58	72.5	9.5	8	2	11.3	23	37.5	24.9	6.5	3	3	1.5	5	180° +5°	+1°/-5°
10	68	85.6	11.6	10	2	14.3	28.4	46	28.2	7.5	4	3	1.6	5.5	200° +5°	+1°/-5°


Datasheet DSM-6 ... 10

Dimensions

Download CAD data → www.festo.com

DSM-... – With flange shaft, adjustable swivel angle and position sensing

DSM-T... – With flange shaft, tandem rotary vanes, adjustable swivel angle and position sensing



[1] Proximity switch not included in the scope of delivery. Observe fitting space for proximity switch and cable guide

[2] Position of the magnet






[3] Max. tightening torque for sensor bracket screws
→ table below

 **Note**






The swivel angle is infinitely adjustable over the entire swivel range. the 6 mm can only be adjusted symmetrically around the centre position.

Size	D8 Ø	D9 Ø	L1		L3	L4	L5	L6		L7	Tightening torque [Nm]
			DSM-...	DSM-T...				DSM-...	DSM-T...		
6	29.4	17.3	65	77.5	4	2	9.8	21	33.5	19.5	0.19
8	37.4	19.3	73.5	88	4	2	11.3	23	37.5	19.5	0.32
10	46.4	22.3	83	100.6	4	2	14.3	28.4	46	19.5	0.44


Datasheet DSM-6 ... 10

Ordering data		Key features	Swivel angle	Size [mm]	Part No.	Type	
Semi-rotary drive							
Spigot shaft							
	Elastic cushioning rings/plates at both ends	90°	6	173188	DSM-6-90-P		
			8	173190	DSM-8-90-P		
			10	173192	DSM-10-90-P		
		180°	6	173189	DSM-6-180-P		
			8	173191	DSM-8-180-P		
			10	173193	DSM-10-180-P		
		240°	10	173194	DSM-10-240-P		
			- Position sensing - Elastic cushioning rings/plates at both ends	90°	6	173195	DSM-6-90-P-A
					8	173197	DSM-8-90-P-A
10	173199				DSM-10-90-P-A		
180°	6			173196	DSM-6-180-P-A		
	8			173198	DSM-8-180-P-A		
	10			173200	DSM-10-180-P-A		
240°	10			173201	DSM-10-240-P-A		
	- Adjustable swivel angle - Elastic cushioning rings/plates at both ends			180°	6	175827	DSM-6-180-P-A-FF
					8	175828	DSM-8-180-P-A-FF
		200°	10	175829	DSM-10-240-P-A-FF		
				- Position sensing - Adjustable swivel angle - Elastic cushioning rings/plates at both ends	180°	6	175830
8	175831	DSM-8-180-P-A-FF					
200°	10	175832			DSM-10-240-P-A-FF		
		- Tandem rotary vanes - Elastic cushioning rings/plates at both ends			90°	6	1564894
8						1563451	DSM-T-8-90-P
10						1559484	DSM-T-10-90-P
180°			6	1565579	DSM-T-6-180-P		
			8	1564407	DSM-T-8-180-P		
			10	1561689	DSM-T-10-180-P		
240°			10	1562093	DSM-T-10-240-P		

Datasheet DSM-6 ... 10

Ordering data		Key features	Swivel angle	Size [mm]	Part No.	Type
Semi-rotary drive						
Flanged shaft						
	Elastic cushioning rings/plates at both ends	90°	6	185928	DSM-6-90-P-FW	
			8	185934	DSM-8-90-P-FW	
			10	185940	DSM-10-90-P-FW	
		180°	6	185929	DSM-6-180-P-FW	
			8	185935	DSM-8-180-P-FW	
			10	185941	DSM-10-180-P-FW	
		240°	10	185942	DSM-10-240-P-FW	
	- Position sensing - Elastic cushioning rings/plates at both ends	90°	6	185930	DSM-6-90-P-A-FW	
			8	185936	DSM-8-90-P-A-FW	
			10	185943	DSM-10-90-P-A-FW	
		180°	6	185931	DSM-6-180-P-A-FW	
			8	185937	DSM-8-180-P-A-FW	
			10	185944	DSM-10-180-P-A-FW	
		240°	10	185945	DSM-10-240-P-A-FW	
	- Adjustable swivel angle - Elastic cushioning rings/plates at both ends	180°	6	185932	DSM-6-180-P-FF-FW	
			8	185938	DSM-8-180-P-FF-FW	
		200°	10	185946	DSM-10-240-P-FF-FW	
	- Position sensing - Adjustable swivel angle - Elastic cushioning rings/plates at both ends	180°	6	185933	DSM-6-180-P-A-FF-FW	
			8	185939	DSM-8-180-P-A-FF-FW	
		200°	10	185947	DSM-10-240-P-A-FF-FW	
	- Tandem rotary vanes - Elastic cushioning rings/plates at both ends	90°	6	1565425	DSM-T-6-90-P-FW	
			8	1564334	DSM-T-8-90-P-FW	
			10	1560818	DSM-T-10-90-P-FW	
		180°	6	1565483	DSM-T-6-180-P-FW	
			8	1564669	DSM-T-8-180-P-FW	
			10	1561556	DSM-T-10-180-P-FW	
		240°	10	1562318	DSM-T-10-240-P-FW	

Peripherals overview DSM-12 ... 63



Peripherals overview DSM-12 ... 63

Accessories	For size	Description	→ Page/Internet
[1] Freewheel unit FLSM	12 ... 40	- For synchronised rotary movement in one direction - Only in combination with swivel module DSM with spigot shaft	50
[2] Push-on flange FWSR	12 ... 40	For retrofitting on swivel module DSM with spigot shaft	51
[3] Mounting plate HSM	12 ... 40	For foot or flange mounting	52
[4] Push-in fitting QS	12 ... 63	For connecting tubing with standard O.D.	qs
[5] One-way flow control valve GRLA	12 ... 63	For regulating speed	57
[6] Cushioning mount DSM-B	12 ... 63	- For fastening elastic cushioning elements or shock absorbers - Included in the scope of delivery for semi-rotary drive DSM-...-P/P1/CC	53
[7] Cushioning kit DSM-...-P	12 ... 63	- Elastic cushioning components with fixed stop - Included in the scope of delivery for semi-rotary drive DSM-...-P	46
[8] Shock absorber DVEF	12 ... 63	- Adjustable, elastic cushioning components with fixed stop - Included in the scope of delivery for semi-rotary drive DSM-...-P1	46
[9] Shock absorber DYSC	12 ... 63	- Self-adjusting shock absorbers with fixed stop - Included in the scope of delivery for semi-rotary drive DSM-...-CC	46
[10] Sensor bracket SL-DSM-B	12 ... 40	For mounting the proximity switch SME/SMT-10	54
[11] Proximity switch SME/SMT-10	12 ... 40	For sensing the end positions	54
[12] Sensor bracket SL-DSM-63-B	63	For mounting the proximity switch SME/SMT-8	54
[13] Proximity switch SME/SMT-8	63	For sensing the end positions	55
[14] Sensor bracket SL-DSM-S	12 ... 40	For mounting the inductive proximity sensor SIEN	54
[15] Proximity switch SIEN	12 ... 40	Inductive proximity switch for sensing the end positions	56
[16] Cover cap AKM	12 ... 40	- Reduces the risk of injury in the swivel range of the stop lever - Cannot be used in combination with inductive proximity sensor SIEN	52
[17] Centring sleeve ZBH	12 ... 63	For centring the drive	57
[18] Centring sleeve ZBH	12 ... 63	For centring attachments on the rotating plate	57
[19] Centring sleeve/disc ZBH/SLZZ	12, 16, 25, 40, 63	For centring attachments in the middle of the rotating plate	57
[20] Adapter kit HAPG, DHAA	12 ... 40	For drive/gripper connections	Gripper

Type codes DSM-12 ... 63

001	Series	
DSM	Semi-rotary drive	

002	Design type	
	Standard	
T	Tandem vane	

003	Size	
12	12	
16	16	
25	25	
32	32	
40	40	
63	63	

004	Nominal swivel angle [°]	
240	240	
246	246	
270	270	

005	Cushioning	
	None	
P	Elastic cushioning rings/plates on both sides	
P1	Elastic cushioning components, at both ends, adjustable	
CC	Shock absorber at both ends, self-adjusting	


006	Shaft	
	Spigot shaft	
FW	Flanged shaft	
HD	Flange shaft for high load torques	

007	Position sensing	
A	For proximity sensor	


008	Variant	
B	B-series	

Datasheet DSM-12 ... 63

Function



Size
12 ... 63



General technical data							
Size	12	16	25	32	40	63	
Pneumatic connection	M5			G1/8		G1/4	
Design	Vane						
Cushioning							
DSM-...-P	Elastic cushioning, at both ends						
DSM-...-P1	Adjustable elastic cushioning at both ends						
DSM-...-CC	Shock absorber, self-adjusting at both ends						
Type of mounting	With female thread						
Mounting position	Any						
Swivel angle							
DSM-... [°]	270						
DSM-...-P [°]	270/262 ¹⁾		270				
DSM-...-P1 [°]	246				240		
DSM-...-CC [°]	246				240		
Swivel angle adjustment							
DSM-...-P [°]	−6						
DSM-...-P1 [°]	−6						
DSM-...-CC [°]	−3						
Cushioning angle							
DSM-...-P1 [°]	10	9	7.5	6.5	6.5	6	
DSM-...-CC [°]	15	12	10	12	16	17.5	
Repetition accuracy							
DSM-...-P [°]	1						
DSM-...-P1 [°]	0.1						
DSM-...-CC [°]	0.1						

1) Restricted swivel angle in combination with sensor bracket SL-DSM-S-...

Swivel frequency [Hz]						
Size	12	16	25	32	40	63
DSM-... / DSM-T-...						
With max. swivel angle						
DSM-...-P	2					1.6
DSM-...-P1	2					1.6
DSM-...-CC	1.5	1			0.7	0.6
With smaller swivel angle						
DSM-...-CC	2	1.5				
DSM-...-HD						
With max. swivel angle						
DSM-...-P1	1.5					1
DSM-...-CC	1			0.5		

Datasheet DSM-12 ... 63

Operating and environmental conditions						
Size	12	16	25	32	40	63
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]					
Operating pressure						
DSM-... [bar]	2 ... 10	1.8 ... 10	1.5 ... 10			
DSM-T... [bar]	2.5 ... 10		2 ... 10			
DSM-...-HD [bar]	3 ... 10		2 ... 10			
Ambient temperature ¹⁾ [°C]	-10 ... +60					
Storage temperature [°C]	20					
ATEX	Selected types → www.festo.com					
CE marking (see declaration of conformity)	To EU Explosion Protection Directive (ATEX)					
UKCA marking (see declaration of conformity)	To UK explosion regulations					
Explosion protection certification outside the EU	EPL Gb (GB)					
	EPL Db (GB)					

1) Note operating range of proximity switches


Weight [g]						
Size	12	16	25	32	40	63
Spigot shaft						
DSM-...-	240	410	620	1250	2400	4220
DSM-...-P	275	470	700	1425	2700	4900
DSM-...-P1	285	475	715	1475	2870	5090
DSM-...-CC	285	480	710	1460	2800	5150
Flanged shaft						
DSM-...-FW	260	450	645	1325	2535	4475
DSM-...-P-FW	293	510	725	1500	2835	5150
DSM-...-P1-FW	303	515	740	1550	3005	5340
DSM-...-CC-FW	300	520	735	1550	2935	5400
Tandem rotary vanes and spigot shaft						
DSM-T...	330	590	890	1865	3570	6050
DSM-T...-P	365	650	970	2040	3870	6730
DSM-T...-CC	375	660	980	2075	3970	6980
Tandem rotary vanes and flange shaft						
DSM-T...-FW	350	630	915	1940	3705	6305
DSM-T...-P-FW	383	690	995	2115	4005	6980
DSM-T...-CC-FW	390	700	1005	2165	4105	7230
Heavy-duty bearing						
DSM-...-HD	375	625	950	1810	3712	5730
DSM-...-P1-HD	420	700	1015	2035	4100	6600
DSM-...-CC-HD	420	705	1010	2020	4030	6660

Datasheet DSM-12 ... 63


Materials

Sectional view


DSM-... / DSM-T-...




DSM-... FW




DSM-...-HD



DSM-T-...



DSM-T-...-FW




Semi-rotary drive

[1]	Housing, flange	Anodised aluminium
[2]	Shaft	Nickel-plated steel
[3]	Vane	Glass fibre-reinforced plastic
[4]	Stop lever	Anodised aluminium
[5]	Rotating plate	Anodised aluminium
–	Fixed stops	Stainless steel
	Screws	Galvanised steel
	Cover cap	Glass fibre-reinforced plastic
	Seals	Polyurethane
	Note on materials	RoHS-compliant
	LABS (PWIS) conformity	VDMA24364-B1/B2-L

Datasheet DSM-12 ... 63

Forces and torques							
Size		12	16	25	32	40	63
Torque at 6 bar							
DSM-...	[Nm]	1.25	2.5	5	10	20	40
DSM-T...	[Nm]	2.5	5	10	20	40	80
DSM-...-HD	[Nm]	1.25	2.5	5	10	20	40
Torque per bar							
DSM-...	[Nm]	0.2	0.41	0.83	1.66	3.33	6.66
DSM-T...	[Nm]	0.4	0.82	1.66	3.33	6.66	13.33
Min. perm. stop radius r	[mm]	15	17	21	28	40	50
Max. perm. stop force F	[N]	90	160	320	480	650	1050
Max. permissible dynamic axial force F_x on drive shaft ¹⁾							
DSM-... / DSM-T...	[N]	18	30	50	75	120	500
DSM-...-HD	[N]	180	290	350	450	950	1300
Max. permissible dynamic radial force F_z on drive shaft ¹⁾							
DSM-... / DSM-T...	[N]	45	75	120	200	350	500
DSM-...-HD	[N]	200	300	450	550	1200	1600
Max. permissible mass moment of inertia							
DSM-...-P	[kgm ²]	→ Page 33					
DSM-...-P1	[kgm ²]	→ Page 34					
DSM-...-CC	[kgm ²]	→ Page 35					

1) The axis of rotation and the centre of the drive shaft are the point of reference for the forces



 **Note**


If the semi-rotary drives DSM-...-A-B are used without a stop system or the maximum mass moment of inertia is exceeded, external stops must be attached. A minimum radius relative to the drive shaft (r_{min}) must be observed. The stop force must not exceed the maximum force.

Datasheet DSM-12 ... 63

Axial eccentricity and concentricity of DSM-...-HD

Axial eccentricity:
Measured on the surface of the rotating plate, at the edge of the plate, when new.

Concentricity:
Measured at the centre of the rotating plate, when new.





Size		12	16	25	32	40	63
Axial eccentricity Y	[mm]	≤ 0.02	≤ 0.02	≤ 0.02	≤ 0.04	≤ 0.04	≤ 0.04
Concentric running Z	[mm]	≤ 0.02	≤ 0.02	≤ 0.02	≤ 0.04	≤ 0.04	≤ 0.04


Datasheet DSM-12 ... 63

Permissible dynamic load for DSM-...-HD

Permissible axial force F_x as a function of distance l





- DSM-12-...-HD
- DSM-16-...-HD
- DSM-25-...-HD




- DSM-32-...-HD
- DSM-40-...-HD
- DSM-63-...-HD

Permissible radial force F_z as a function of distance l



- DSM-12-...-HD
- DSM-16-...-HD
- DSM-25-...-HD




- DSM-32-...-HD
- DSM-40-...-HD
- DSM-63-...-HD


Datasheet DSM-12 ... 63

Mass moment of inertia J as a function of swivel time t
With elastic cushioning components (P)


DSM-12-270-P




DSM-16-270-P




DSM-25-270-P




DSM-32-270-P



DSM-40-270-P



DSM-63-270-P



— 90°
 ····· 180°
 - - - 270°


**Note**

Engineering software
 for calculating inertia
 → www.festo.com

Datasheet DSM-12 ... 63


Mass moment of inertia J as a function of swivel time t
With adjustable, elastic cushioning components (P1)

DSM-12-270-P1




— 90°
····· 180°
--- 246°

DSM-16-270-P1




DSM-25-270-P1




— 90°
····· 180°
--- 246°

DSM-32-270-P1




DSM-40-270-P1



— 90°
····· 180°
--- 240°


DSM-63-270-P1




Datasheet DSM-12 ... 63

Mass moment of inertia J as a function of swivel time t
 With hydraulic shock absorbers (CC)


DSM-12-270-CC




DSM-16-270-CC



DSM-25-270-CC




DSM-32-270-CC




— 90°
 ····· 180°
 - - - 246°

DSM-40-270-CC



DSM-63-270-CC




— 90°
 ····· 180°
 - - - 246°

Datasheet DSM-12 ... 63

Dimensions

Download CAD data → www.festo.com

DSM-... – With spigot shaft



- [1] Featherkey position at 0°
- [2] Compressed air supply ports
- [3] Locking screw for clamping the stop
- [4] Manual override (internal hexagon). The position of the internal hexagon is not defined.
- [5] End-position adjustment

- [6] Lock nut for end-position adjustment
- [7] Infinitely adjustable stops
- [8] Mounting thread for sensor bracket
- [10] Sensor bracket
- [11] End-position adjustment

Datasheet DSM-12 ... 63

Size	B1 ±0.5	B2	B3	B4	D1 ø g7	D2 ø	D3 ø f8	D4
12	19.8	48±0.3	59±0.3	30±0.2	8	15±0.2	24	M3
16	23.5	57±0.3	70±0.3	40±0.2	10	18 _{0.3}	28	M3
25	28	65±0.3	83±0.3	40±0.2	12	20 _{0.3}	30	M4
32	35.5	85±0.3	105±0.3	60±0.3	16	27 _{0.4}	42	M5
40	43.8	105±0.3	130±0.5	80±0.3	20	36 _{0.4}	52	M6
63	50.3	125±0.5	152 ^{+0.2}	80±0.3	25	40±0.3	70	M10

Size	D5	D6	D7 ø	D8	D9	D10	EE
12	M4	M2	78±0.3	M8x1	M4	M4	M5
16	M5	M2	91±0.3	M10x1	M5	M5	M5
25	M6	M2	106±0.3	M10x1	M6	M5	M5
32	M8	M2	135±0.3	M12x1	M8	M5	G1/8
40	M10	M2	168±0.5	M16x1	M10	M6	G1/8
63	M10	M3	200±0.5	M22x1.5	M12	M6	G1/4

Size	H1 ±0.2	L1	L2 +0.6 -0.7	L3	L4 ±0.4	L5	L6	L7
12	29.5	68.3±0.3	24.5	20±0.2	3	10.3+0.2/-0.3	55.5±0.8	5±0.1
16	35	82.7±1	28	23±0.2	2.6	13+0.2/-0.4	67.1±0.9	6.5±0.2
25	41.5	97.5±0.5	36.5	30±0.2	4	15.2+0.2/-0.4	81±1	7.5±0.2
32	52.5	127.1±0.5	51	40±0.2	8	19.2+0.2/-0.4	107±1.1	9.5±0.2
40	65	155.5±0.6	62	50±0.3	8	23.7+0.2/-0.4	131±1.2	12±0.2
63	76	197+0.4/-0.55	75.5	60±0.3	10.5	28.5+0.3/-0.5	159.5±1.2	14±0.2

Size	L8	L9	L10	L13	L14 max.	T1 max.	T2 +2	T3 +0.2
12	16.5	3	22.7	6.5	21.2	8.8	9	8
16	20.2	7.2	26.1	6.5	22	11.2	9	8
25	23.5	2.9	20.7	6.5	17	13.5	10	10
32	30.5	3.8	29.1	6.5	23	18	12.5	12
40	36	3.4	43.5	6.5	36.5	22.5	16	15
63	45	10	72.5	4.5	–	28	22	16

Size	☞ 1	☞ 2	☞ 3	☞ 4	☞ 5	☞ 6	Featherkey to DIN 6885 ¹⁾
12	10	6	2.5	2.5	2.5	2.5	A2x2x16
16	13	8	3	3	3	5	A3x3x18
25	13	8	4	3	3	6	A4x4x25
32	15	10	5	4	4	8	A5x5x36
40	19	10	6	5	5	10	A6x6x45
63	27	10	8	5	–	–	A8x7x50

1) Included in the scope of delivery.

Datasheet DSM-12 ... 63

Size	B1 ±0.5	B2	B3	B4	B5	D1 ∅ f8	D2 ∅	D3 ∅ f8	D4	D5
12	19.8	48±0.3	59±0.3	30±0.2	25	14	15±0.2	24	M5	M4
16	23.5	57±0.3	70±0.3	40±0.2	28	16	18 _{-0.3}	28	M5	M5
25	28	65±0.3	83±0.3	40±0.2	35	20	20 _{-0.3}	30	G1/8	M6
32	35.5	85±0.3	105±0.3	60±0.3	45	28	27 _{-0.4}	42	G1/8	M8
40	43.8	105±0.3	130±0.5	80±0.3	54	36	36 _{-0.4}	52	G1/4	M10
63	50.3	125±0.5	152±0.2	80±0.3	64	38	40±0.3	70	G1/4	M10

Size	D6	D7 ∅	D8	D9	D10 ∅	D11	D12 H13	D13	EE	H1 ±0.2
12	M2	78±0.3	M8x1	M4	33	M3	3.4	4.2	M5	29.5
16	M2	91±0.3	M10x1	M5	38	M4	4.5	4.2	M5	35
25	M2	106±0.3	M10x1	M6	46	M5	5.5	8.6	M5	41.5
32	M2	135±0.3	M12x1	M8	60	M6	6.5	8.6	G1/8	52.5
40	M2	168±0.5	M16x1	M10	70	M8	9	11.5	G1/8	65
63	M3	200±0.5	M22x1.5	M12	88	M8	12	11.5	G1/4	76

Size	L1	L2 +0.5 -0.85	L3 +0.5 -0.62	L4 ±0.4	L5	L6 ±1	L7	L8	L9 -0.2	L10
12	67.3+0.4/-0.65	13	11	3	10.3+0.2/-0.3	44	5±0.1	16.5	2	3±0.1
16	79+0.4/-0.65	15	13	2.6	13+0.2/-0.4	54.1	6.5±0.2	20.2	2	4±0.1
25	90+0.4/-0.65	19.5	16.5	4	15.2+0.2/-0.4	64	7.5±0.2	23.5	3	4.5±0.1
32	115.8+0.4/-0.65	27	23	8	19.2+0.2/-0.4	83	9.5±0.2	30.5	4	6±0.1
40	143.8+0.4/-0.7	33	28	8	23.7+0.2/-0.4	102	12±0.2	36	5	7.5±0.1
63	177.4+0.2/-0.55	37.5	31.5	10.5	28.5+0.3/-0.5	121.5	14±0.2	45	6	9±0.2


Size	L11	L12	L14 max.	T3 +0.2	≈ 1	≈ 2	≈ 3	≈ 4	≈ 5	≈ 6
12	3	22.7	21.2	8	10	8	2.5	2.5	2.5	2.5
16	7.2	26.1	22	8	13	11	3	3	3	5
25	2.9	20.7	17	10	13	13	4	3	3	6
32	3.8	29.1	23	12	15	13	5	4	4	8
40	3.4	43.5	36.5	15	19	19	6	5	5	10
63	10	72.5	–	16	27	22	8	5	–	–

Datasheet DSM-12 ... 63

Dimensions

Download CAD data → www.festo.com

DSM-T... – With spigot shaft and tandem rotary vanes



- [1] Featherkey position at 0°
- [2] Compressed air supply ports
- [3] Locking screw for clamping the stop
- [4] Manual override (internal hexagon). The position of the internal hexagon is not defined.

- [5] End-position adjustment
- [6] Lock nut for end-position adjustment
- [7] Infinitely adjustable stops
- [8] Mounting thread for sensor bracket
- [10] Sensor bracket

Datasheet DSM-12 ... 63

Size	B1 ±0.5	B2	B3	B4	D1 ∅ g7	D2 ∅	D3 ∅ f8
12	19.8	48±0.3	59±0.3	30±0.2	8	15±0.2	24
16	23.5	57±0.3	70±0.3	40±0.2	10	18 _{0.3}	28
25	28	65±0.3	83±0.3	40±0.2	12	20 _{0.3}	30
32	35.5	85±0.3	105±0.3	60±0.3	16	27 _{0.4}	42
40	43.8	105±0.3	130±0.5	80±0.3	20	36 _{0.4}	52
63	50.3	125±0.5	152 ^{+0.2}	80±0.3	25	40±0.3	70

Size	D4	D5	D6	D7 ∅	D8	D9	D10
12	M3	M4	M2	78±0.3	M8x1	M4	M4
16	M3	M5	M2	91±0.3	M10x1	M5	M5
25	M4	M6	M2	106±0.3	M10x1	M6	M5
32	M5	M8	M2	135±0.3	M12x1	M8	M5
40	M6	M10	M2	168±0.5	M16x1	M10	M6
63	M10	M10	M3	200±0.5	M22x1.5	M12	M6

Size	EE	H1 ±0.2	L1	L2 +0.6 -0.7	L3	L4 ±0.4	L5
12	M5	29.5	87.3±0.3	24.5	20±0.2	3	10.3+0.2/-0.3
16	M5	35	106.6±1	28	23±0.2	2.6	13+0.2/-0.4
25	M5	41.5	125.5±0.5	36.5	30±0.2	4	15.2+0.2/-0.4
32	G1/8	52.5	164±0.5	51	40±0.2	8	19.2+0.2/-0.4
40	G1/8	65	200.5±0.6	62	50±0.3	8	23.7+0.2/-0.4
63	G1/4	76	254.4+0.4/-0.55	75.5	60±0.3	10.5	28.5+0.3/-0.5

Size	L6	L7	L8	L9	L10	L13	T1 max.
12	74.5±0.8	5±0.1	35.5	3	22.7	6.5	8.8
16	91±0.9	6.5±0.2	44.1	7.2	26.1	6.5	11.2
25	109±1	7.5±0.2	51.5	2.9	20.7	6.5	13.5
32	144±1.1	9.5±0.2	67.4	3.8	29.1	6.5	18
40	176±1.2	12±0.2	81	3.4	43.5	6.5	22.5
63	216.5±1.2	14±0.2	99	10	72.5	4.5	28

Size	T2 +2	T3 +0.2	≡ 1	≡ 2	≡ 3	≡ 4	Featherkey to DIN 6885 ¹⁾
12	9	8	10	6	2.5	2.5	A2x2x16
16	9	8	13	8	3	3	A3x3x18
25	10	10	13	8	4	3	A4x4x25
32	12.5	12	15	10	5	4	A5x5x36
40	16	15	19	10	6	5	A6x6x45
63	22	16	27	10	8	5	A8x7x50


1) Included in the scope of delivery.

Datasheet DSM-12 ... 63

Dimensions

Download CAD data → www.festo.com

DSM-T-...-FW – with flange shaft tandem rotary vanes



- | | |
|--|---|
| [1] Flange shaft with through-hole | [6] Lock nut for end-position adjustment |
| [2] Compressed air supply ports | [7] Infinitely adjustable stops |
| [3] Locking screw for clamping the stop | [8] Mounting thread for sensor bracket |
| [4] Manual override (external hexagon). The position of the external hexagon is not defined. | [9] Position of marking corresponds to position of stop |
| [5] End-position adjustment | [10] Sensor bracket |

Datasheet DSM-12 ... 63

Size	B1 ±0.5	B2	B3	B4	B5	D1 ∅ f8	D2 ∅	D3 ∅ f8	D4
12	19.8	48±0.3	59±0.3	30±0.2	25	14	15±0.2	24	M5
16	23.5	57±0.3	70±0.3	40±0.2	28	16	18 _{-0.3}	28	M5
25	28	65±0.3	83±0.3	40±0.2	35	20	20 _{-0.3}	30	G1/8
32	35.5	85±0.3	105±0.3	60±0.3	45	28	27 _{-0.4}	42	G1/8
40	43.8	105±0.3	130±0.5	80±0.3	54	36	36 _{-0.4}	52	G1/4
63	50.3	125±0.5	152±0.2	80±0.3	64	38	40±0.3	70	G1/4

Size	D5	D6	D7 ∅	D8	D9	D10 ∅	D11	D12 H13	D13
12	M4	M2	78±0.3	M8x1	M4	33	M3	3.4	4.2
16	M5	M2	91±0.3	M10x1	M5	38	M4	4.5	4.2
25	M6	M2	106±0.3	M10x1	M6	46	M5	5.5	8.6
32	M8	M2	135±0.3	M12x1	M8	60	M6	6.5	8.6
40	M10	M2	168±0.5	M16x1	M10	70	M8	9	11.5
63	M10	M3	200±0.5	M22x1.5	M12	88	M8	12	11.5

Size	EE	H1 ±0.2	L1	L2 +0.5 -0.85	L3 +0.5 -0.62	L4 ±0.4	L5	L6 ±1	L7
12	M5	29.5	86.3+0.4/-0.65	13	11	3	10.3+0.2/-0.3	63	5±0.1
16	M5	35	103+0.4/-0.65	15	13	2.6	13+0.2/-0.4	78	6.5±0.2
25	M5	41.5	118+0.4/-0.65	19.5	16.5	4	15.2+0.2/-0.4	92	7.5±0.2
32	G1/8	52.5	152.8+0.4/-0.65	27	23	8	19.2+0.2/-0.4	120	9.5±0.2
40	G1/8	65	188.8+0.4/-0.7	33	28	8	23.7+0.2/-0.4	147	12±0.2
63	G1/4	76	234.4+0.2/-0.55	37.5	31.5	10.5	28.5+0.3/-0.5	178.5	14±0.2


Size	L8	L9 -0.2	L10	L11	L12	T3 +0.2	≈C 1	≈C 2	≈C 3	≈C 4
12	35.5	2	3±0.1	3	22.7	8	10	8	2.5	2.5
16	44.1	2	4±0.1	7.2	26.1	8	13	11	3	3
25	51.5	3	4.5±0.1	2.9	20.7	10	13	13	4	3
32	67.4	4	6±0.1	3.8	29.1	12	15	13	5	4
40	81	5	7.5±0.1	3.4	43.5	15	19	19	6	5
63	99	6	9±0.2	10	72.5	16	27	22	8	5

Datasheet DSM-12 ... 63

Dimensions

Download CAD data → www.festo.com

DSM-...-HD – with heavy-duty bearing



- [1] Supply ports
- [2] Locking screw for clamping the stop
- [3] Manual override (external hexagon). The position of the external hexagon is not defined.
- [4] End-position adjustment
- [5] Lock nut for end-position adjustment
- [6] Mounting thread for sensor bracket
- [7] Infinitely adjustable stops
- [8] Flange shaft with through-hole
- [9] Drilled hole for centring sleeve ZBH
- [10] Sensor bracket

* Size 12 ... 25
 ** Size 32 ... 63

Datasheet DSM-12 ... 63

Size	B1 ±0.3	B2 ±0.3	B3 ±0.5	D1 ¹⁾	D2 ²⁾ ∅	D3 ±0.02	D4	D5 DSM-...-P1/DSM-...-CC
12	59	48	19.8	M5	–	22	36	M8x1
16	70	57	23.5	M5	–	28	45	M10x1
25	83	65	28	G1/8	–	30	50	M10x1
32	105	85	35.5	15	G1/8	42	65	M12x1
40	130	105	43.8	20	G1/4	56	90	M16x1
63	152	125	50.3	20	G1/4	70	105	M22x1.5

Size	D6	D7 H7	D8	D9 f8	D10 ±0.5	D11	D12	D13	D14
12	M3	5	57.5	58	78	M2	M5	M4	M4
16	M4	7	68.5	68	91	M2	M5	M5	M5
25	M5	7	81.5	76	106	M2	G1/8	M6	M6
32	M5	7	103.5	96	135	M2	G1/8	M8	M8
40	M8	12	128	126	168	M2	G1/4	M10	M10
63	M8	12	149	150	200	M3	G1/4	M12	M10

Size	D15 H7	D16	D17 H8	D18	EE	H1 ±0.03	H2 max.		L1 +0.4 –0.65	L2 +1
							DSM-...-P1	DSM-...-CC		
12	7	6	12	3.3	M5	30	21.2	22.7	76.3	53
16	7	8	12	4.2	M5	40	22	26.1	88.5	63.6
25	9	10	15	5.1	M5	40	17	20.7	98.7	72.7
32	12	11	20	6.8	G1/8	60	23	29.1	121	88.5
40	12	15	25	8.5	G1/8	80	36.5	43.5	154	112
63	12	18	25	10.2	G1/4	80	44	72.5	185.5	129.5



Size	L3	L4 ±0.1	L5 ±0.2	L6 ±0.1	T1 +0.1	T2	T3	T4 +0.1	T5	T6 +0.1
12	22.3	10	10	4	1.5	9	9	1.2	6	2.5
16	27.6	10	10	4	1.5	9	9	1.5	6	2.5
25	33.4	10	10	6	2	12	8	1.5	8	2.5
32	39.6	10	12	6	2.5	14	9.5	1.5	8	2.8
40	52.7	12	14	5.5	2.5	17	15	2.5	12	2.8
63	58	14	16	10	2.5	18	14	2.5	15	2.8

Size	T7	T8	T9	≈ 1	≈ 2	≈ 3 h13	≈ 4		≈ 5 DSM-...-P1	W1
							DSM-...-P1	DSM-...-CC		
12	6.3	5.5	12	10	2.5	8	5	2.5	2.5	45°
16	8.5	6	14	13	3	11	6	3	3	45°
25	10	5.3	16	13	4	13	6	3	3	45°
32	9.5	–	20	15	5	13	8	4	4	45°
40	15	–	24	19	6	19	8	5	5	45°
63	18	–	28	27	8	22	10	5	5	45°



1) Thread for compressed air through-feed with size 12 ... 25

2) Thread for compressed air through-feed with size 32 ... 63


Datasheet DSM-12 ... 63

Ordering data – DSM-..., semi-rotary drive					
Semi-rotary drive	Key features	Swivel angle	Size	Part no.	Type
Spigot shaft					
	Without cushioning components	270°	12	547591	DSM-12-270-A-B
			16	547592	DSM-16-270-A-B
			25	547593	DSM-25-270-A-B
			32	547594	DSM-32-270-A-B
			40	547595	DSM-40-270-A-B
			63	552083	DSM-63-270-A-B
	P With elastic cushioning components	270°	12	547570	DSM-12-270-P-A-B
			16	547574	DSM-16-270-P-A-B
			25	547578	DSM-25-270-P-A-B
			32	547582	DSM-32-270-P-A-B
			40	547586	DSM-40-270-P-A-B
			63	552079	DSM-63-270-P-A-B
	P1 With adjustable, elastic cushioning components	246°	12	566203	DSM-12-270-P1-A-B
			16	566205	DSM-16-270-P1-A-B
			25	566207	DSM-25-270-P1-A-B
			32	566209	DSM-32-270-P1-A-B
		240°	40	566211	DSM-40-270-P1-A-B
			63	566213	DSM-63-270-P1-A-B
	CC With shock absorber	246°	12	547572	DSM-12-270-CC-A-B
			16	547576	DSM-16-270-CC-A-B
			25	547580	DSM-25-270-CC-A-B
			32	547584	DSM-32-270-CC-A-B
		240°	40	547588	DSM-40-270-CC-A-B
			63	552081	DSM-63-270-CC-A-B
Flanged shaft					
	Without cushioning components	270°	12	547596	DSM-12-270-FW-A-B
			16	547597	DSM-16-270-FW-A-B
			25	547598	DSM-25-270-FW-A-B
			32	547599	DSM-32-270-FW-A-B
			40	547600	DSM-40-270-FW-A-B
			63	552084	DSM-63-270-FW-A-B
	P With elastic cushioning components	270°	12	547571	DSM-12-270-P-FW-A-B
			16	547575	DSM-16-270-P-FW-A-B
			25	547579	DSM-25-270-P-FW-A-B
			32	547583	DSM-32-270-P-FW-A-B
			40	547587	DSM-40-270-P-FW-A-B
			63	552080	DSM-63-270-P-FW-A-B
	P1 With adjustable, elastic cushioning components	246°	12	566204	DSM-12-270-P1-FW-A-B
			16	566206	DSM-16-270-P1-FW-A-B
			25	566208	DSM-25-270-P1-FW-A-B
			32	566210	DSM-32-270-P1-FW-A-B
		240°	40	566212	DSM-40-270-P1-FW-A-B
			63	566214	DSM-63-270-P1-FW-A-B
	CC Shock absorber	246°	12	547573	DSM-12-270-CC-FW-A-B
			16	547577	DSM-16-270-CC-FW-A-B
			25	547581	DSM-25-270-CC-FW-A-B
			32	547585	DSM-32-270-CC-FW-A-B
		240°	40	547589	DSM-40-270-CC-FW-A-B
			63	552082	DSM-63-270-CC-FW-A-B

Datasheet DSM-12 ... 63

Ordering data – DSM-T-..., semi-rotary drive with tandem rotary vanes							
Semi-rotary drive	Key features	Swivel angle	Size	Part no.	Type		
Spigot shaft							
	Without cushioning components	270°	12	1145122	DSM-T-12-270-A-B		
			16	1145123	DSM-T-16-270-A-B		
			25	1145124	DSM-T-25-270-A-B		
			32	1145125	DSM-T-32-270-A-B		
			40	1145126	DSM-T-40-270-A-B		
			63	1145127	DSM-T-63-270-A-B		
	P With elastic cushioning components	270°	12	1145086	DSM-T-12-270-P-A-B		
			16	1145092	DSM-T-16-270-P-A-B		
			25	1145098	DSM-T-25-270-P-A-B		
			32	1145104	DSM-T-32-270-P-A-B		
			40	1145110	DSM-T-40-270-P-A-B		
			63	1145116	DSM-T-63-270-P-A-B		
	CC With shock absorber	246°	12	1145088	DSM-T-12-270-CC-A-B		
			16	1145094	DSM-T-16-270-CC-A-B		
			25	1145100	DSM-T-25-270-CC-A-B		
			32	1145106	DSM-T-32-270-CC-A-B		
		240°	40	1145112	DSM-T-40-270-CC-A-B		
			63	1145118	DSM-T-63-270-CC-A-B		
Flanged shaft							
			Without cushioning components	270°	12	1145128	DSM-T-12-270-FW-A-B
	16	1145129			DSM-T-16-270-FW-A-B		
	25	1145130			DSM-T-25-270-FW-A-B		
	32	1145131			DSM-T-32-270-FW-A-B		
	40	1145132			DSM-T-40-270-FW-A-B		
	63	1145133			DSM-T-63-270-FW-A-B		
	P With elastic cushioning components	270°	12	1145087	DSM-T-12-270-P-FW-A-B		
			16	1145093	DSM-T-16-270-P-FW-A-B		
			25	1145099	DSM-T-25-270-P-FW-A-B		
			32	1145105	DSM-T-32-270-P-FW-A-B		
			40	1145111	DSM-T-40-270-P-FW-A-B		
			63	1145117	DSM-T-63-270-P-FW-A-B		
	CC Shock absorber	246°	12	1145089	DSM-T-12-270-CC-FW-A-B		
			16	1145095	DSM-T-16-270-CC-FW-A-B		
			25	1145101	DSM-T-25-270-CC-FW-A-B		
			32	1145107	DSM-T-32-270-CC-FW-A-B		
		240°	40	1145113	DSM-T-40-270-CC-FW-A-B		
			63	1145119	DSM-T-63-270-CC-FW-A-B		

Datasheet DSM-12 ... 63

Ordering data – DSM-...-HD, semi-rotary drive with heavy-duty guide					
Semi-rotary drive	Key features	Swivel angle	Size	Part no.	Type
Heavy-duty bearing					
	Without cushioning components	270°	12	1369110	DSM-12-270-HD-A-B
			16	1369111	DSM-16-270-HD-A-B
			25	1369112	DSM-25-270-HD-A-B
			32	1369113	DSM-32-270-HD-A-B
			40	1369114	DSM-40-270-HD-A-B
			63	1369115	DSM-63-270-HD-A-B
	P1 With adjustable, elastic cushioning components	246°	12	1369116	DSM-12-270-P1-HD-A-B
			16	1369117	DSM-16-270-P1-HD-A-B
			25	1369118	DSM-25-270-P1-HD-A-B
			32	1369119	DSM-32-270-P1-HD-A-B
		240°	40	1369120	DSM-40-270-P1-HD-A-B
			63	1369121	DSM-63-270-P1-HD-A-B
	CC With shock absorber	246°	12	1369122	DSM-12-270-CC-HD-A-B
			16	1369123	DSM-16-270-CC-HD-A-B
			25	1369124	DSM-25-270-CC-HD-A-B
			32	1369125	DSM-32-270-CC-HD-A-B
		240°	40	1369126	DSM-40-270-CC-HD-A-B
			63	1369127	DSM-63-270-CC-HD-A-B

Accessories

Free wheel unit FLSM

For size 6, 8


Material:

Housing: Anodised aluminium

Shaft, sleeve:

Size 6, 8: steel

Size 10: hardened steel




Note


The minimum possible rotation angle is 3°. However, the switching accuracy is dependent on speed and load.

Dimensions and ordering data

FLSM-6/8



FLSM-10



For size	B3	B4	D1 ø g7	D3 ø h8	D4	D5	D6 ø ±0.3	L1	L2	L3	L4	L6 ±0.2
6	29.5	23	4	14	—	M3	28	85.8	36 ±0.1	10.8	10	2
8	37	24	5	16	—	M3	30	94.5	37.5 ±0.1	14	13	2
10	45	38	6	20	M2.5	M3	43	101	30 ±0.1	16.7	—	3.5

For size	L8 ±0.1	L9	T1	T2	T3	T4	Featherkey to DIN 6885	CRC ¹⁾	Weight [g]	Direction of rotation	Part no.	Type
6	43	12.8	—	—	5	3.5	—	2	100	Anticlockwise rotation	188523	FLSM-6-L
										Clockwise rotation	188522	FLSM-6-R
8	44.5	16	—	—	6	4.5	—	2	125	Anticlockwise rotation	188525	FLSM-8-L
										Clockwise rotation	188524	FLSM-8-R
10	40	20.2	6.8	7	8	—	A2x2x12	2	160	Anticlockwise rotation	188527	FLSM-10-L
										Clockwise rotation	188526	FLSM-10-R

1) More information: www.festo.com/x/topic/crc

Accessories


Free wheel unit FLSM

For size 12 ... 40

Material:

Housing: Anodised aluminium

Shaft, sleeve: Hardened steel




Note

The minimum possible rotation angle is 3°. However, the switching accuracy is dependent on speed and load.

Dimensions and ordering data

FLSM-12 ... 40



For size	B3	B4 ±0.15	D1 Ø g7	D3 Ø h8	D4	D5	D6 Ø ±0.3	L1	L2	L3	L6 +0.2	L8 ±0.1
12	55	42	8	25	M3	M3	48.5	125	37 ±0.4	20	3.5	47.3
16	65	50	10	24	M3	M4	60	137	34 ±0.4	23	3.5	47
25	80	60	12	28	M4	M6	70	152	34 ±0.4	30	3.5	49
32	100	83	16	42	M5	M6	95	197.8	42.8 ±0.4	40	7.2	60.8
40	120	96	20	52	M6	M8	110	244.5	54 ±0.4	50	6	77

For size	L9	T1	T2	T3	Feather key to DIN 6885	CRC ¹⁾	Weight [g]	Direction of rotation	Part no.	Type
12	24.5	8.8	9	8	A2x2x16	2	300	Anticlockwise rotation	164229	FLSM-12-L
								Clockwise rotation	164234	FLSM-12-R
16	27.4	11.2	9	10	A3x3x18	2	450	Anticlockwise rotation	164230	FLSM-16-L
								Clockwise rotation	164235	FLSM-16-R
25	34	13.5	10	15	A4x4x25	2	650	Anticlockwise rotation	164231	FLSM-25-L
								Clockwise rotation	164236	FLSM-25-R
32	48.5	18	12.5	15	A5x5x36	2	1500	Anticlockwise rotation	164232	FLSM-32-L
								Clockwise rotation	164237	FLSM-32-R
40	58	22.5	16	15	A6x6x45	2	2350	Anticlockwise rotation	164233	FLSM-40-L
								Clockwise rotation	164238	FLSM-40-R

1) More information: www.festo.com/x/topic/crc


Accessories

Push-on flange FWSR

Material:
Anodised wrought aluminium alloy




FLSM-6/8



[1] Threaded pin M3x5 DIN 916

FLSM-10



Dimensions and ordering data

For size	B5	D11	D12 Ø H13	D13 Ø	D14 Ø	D15 Ø +0.4
6	16	M3	3.4	8 _{g7}	23	10
8	21	M3	3.4	11 _{g7}	27	12
10	21	M3	3.4	11 _{f8}	30 _{-0.5}	12
12	25	M3	3.4	14 _{f8}	35 _{-0.5}	15
16	28	M4	4.5	16 _{f8}	40 _{-0.5}	17
25	35	M5	5.5	20 _{f8}	50 _{-0.5}	23
32	45	M6	6.5	28 _{f8}	60 _{-0.5}	28
40	54	M8	9	36 _{f8}	70 _{-0.5}	38


For size	L9	L10	L11	L12	CRC ¹⁾	Weight [g]	Part no.	Type
6	10.5	3	1.5	45	2	6	185948	FWSR-6
8	12.5	3	1.5	51	2	8	185949	FWSR-8
10	22	3	1.6	68.6	2	10	32798	FWSR-10
12	25	3	3	85.5	2	19	14659	FWSR-12
16	28	5	3	98.8	2	30	13239	FWSR-16
25	38	8	3	116.5	2	70	13240	FWSR-25
32	48	10	4	151.5	2	120	13241	FWSR-32
40	60	11	5	186.5	2	240	14656	FWSR-40

1) More information: www.festo.com/x/topic/crc

Accessories

Mounting plate HSM

Material:
Aluminium




Dimensions and ordering data											
For size	B6	D16 Ø	D17 Ø	H2	L12	L13	T4	CRC ¹⁾	Weight [g]	Part no.	Type
12	20	8	4.5	10	84	72	4.6	2	48	165571	HSM-12
16	28	10	5.5	10	98	84	5.7	2	80	165572	HSM-16
25	30	11	6.6	10	110	95	6.8	2	94	165573	HSM-25
32	40	15	9	15	145	125	9	2	246	165574	HSM-32
40	45	18	11	20	180	155	11	2	459	165575	HSM-40

1) More information: www.festo.com/x/topic/crc

Cover cap AKM



Material:
Polyamide

Cannot be used in combination with
inductive proximity sensor SIEN.




Dimensions and ordering data						
For size	D1 Ø	L1			Part no.	Type
		DSM-...	DSM-T...	DSM-...-HD...		
12	59	56.2±1.2	75.2±1.2	68.2±1.2	549194	AKM-12
16	70	68±1.2	92±1.2	82.6±1.2	549195	AKM-16
25	83	73.4±1.2	101.5±1.2	91.6±1.2	549196	AKM-25
32	105	89.7±1.5	126.7±1.5	110.2±1.5	549197	AKM-32
40	130	107.1±1.5	152.1±1.5	136.1±1.5	549198	AKM-40


Accessories


Ordering data					
	For size	Description	Part no.	Type	PU ¹⁾
Cushioning kit					
	12	- Elastic cushioning components with fixed stop - Included in the scope of delivery for semi-rotary drive DSM-...-P	550657	DSM-12-P-B	2
	16, 25		550658	DSM-16/25-P-B	
	32		550659	DSM-32-P-B	
	40		550660	DSM-40-P-B	
	63		552086	DSM-63-P-B	
Shock absorber			Datasheets → Internet: dyef		
	12	- Adjustable, elastic cushioning components with fixed stop - Included in the scope of delivery for semi-rotary drive DSM-...-P1	548373	DYEF-M8-Y1F	1
	16, 25		548374	DYEF-M10-Y1F	
	32		548375	DYEF-M12-Y1F	
	40		548377	DYEF-M16-Y1F	
	63		1113706	DYEF-M22-Y1F	
Shock absorber			Datasheets → Internet: dysc		
	12	- Self-adjusting shock absorbers with fixed stop - Included in the scope of delivery for semi-rotary drive DSM-...-CC	548011	DYSC-5-5-Y1F	1
	16, 25		548012	DYSC-7-5-Y1F	
	32		548013	DYSC-8-8-Y1F	
	40		548014	DYSC-12-12-Y1F	
	63		553593	DYSC-16-18-Y1F	
Cushioning mount					
	12	For mounting flexible cushioning elements DSM-...-P-B, DYEF or shock absorber DYSC	547900	DSM-12-B	2
	16		547901	DSM-16-B	
	25		547902	DSM-25-B	
	32		547903	DSM-32-B	
	40		547904	DSM-40-B	
	63		552085	DSM-63-B	

1) Packaging unit

Ordering data – Position sensor					
	For size	Description	Part no.	Type	PU ¹⁾
	6	• For sensing the end positions	2619969	SRBS-Q12-6-E270-EP-1-S-M8	1
	8	• Simple and reliable operation using one pushbutton	2619972	SRBS-Q12-8-E270-EP-1-S-M8	
	10	• Only one connecting cable required	2412001	SRBS-Q1-10-E270-EP-1-S-M8	
		• Possible sensing range: 0 ... 270°			
		• Repetition accuracy: ≤ 1°			
		• Number of switching outputs: 2			
		• Switching output: PNP/NPN			
		• Switching element: N/O contact / N/C contact			

Accessories


Ordering data – Kits				
	For size	Description	Part no.	Type
Mounting kit			Datasheets → Internet: wsm	
	6	Via proximity switches SME/SMT-10	173205	WSM-6-SME-10
	8		173206	WSM-8-SME-10
	10		173207	WSM-10-SME-10
Stop kit			Datasheets → Internet: ksm	
	6	For adjusting the swivel angle, max. 180°	175833	KSM-6
	8		175834	KSM-8
	10	For adjusting the swivel angle, max. 200°	175835	KSM-10

Ordering data – Adapter kit				
	For size	Description	Part no.	Type
	6	For attaching mounting kit WSM to stop kit KSM	3617044	DADP-AK-Q1-6
	8		3617045	DADP-AK-Q1-8
	10		3617046	DADP-AK-Q1-10

Ordering data – Sensor brackets					
	For size	Description	Part no.	Type	PU ¹⁾
	12, 16, 25, 32, 40	For proximity switches SME-/SMT-10	550661	SL-DSM-B	2
	63	For proximity switches SME-/SMT-8	552088	SL-DSM-63-B	2
	12, 16, 25, 32, 40	For inductive proximity sensors SIEN-M5	1130882	SL-DSM-S-M5-B	2
		For inductive proximity sensors SIEN-M8	1132360	SL-DSM-S-M8-B	


1) Packaging unit

Proximity switches for size 6, 8, 10, 12, 25, 32, 40 (not suitable for size 16)


Ordering data – Proximity switch for C-slot, magneto-resistive Datasheets → Internet: smt						
	Type of mounting	Switching output	Electrical connection, Outlet direction of connection	Cable length [m]	Part no.	Type
N/O						
	With size 6, 8, 10: Via mounting kit WSM-...SME-10 With size 12, 25, 32, 40: Mounted on the DSM using sensor bracket SL-DSM-B	PNP	Cable, 3-core, lengthwise	2.5	551373	SMT-10M-PS-24V-E-2.5-L-OE
			Plug M8x1, 3-pin, in-line	0.3	551375	SMT-10M-PS-24V-E-0.3-L-M8D

Accessories



Proximity switch for size 6 ... 40


Ordering data – Proximity switch for C-slot, magnetic reed							Datasheets → Internet: sme
	Type of mounting	Switching output	Electrical connection, Outlet direction of connection	Cable length [m]	Part no.	Type	
N/O							
	With size 6, 8, 10: Via mounting kit WSM-...SME-10 With size 12 ... 40: Mounted on the DSM using sensor bracket SL-DSM-B	Contacting	Cable, 3-core, lengthwise	2.5	173210	SME-10-KL-LED-24	
			Plug M8x1, 3-pin, in-line	0.3	173212	SME-10-SL-LED-24	

Proximity switch for size 12 ... 40

Ordering data – Proximity switch for C-slot, magnetic reed							Datasheets → Internet: sme
	Type of mounting	Switching output	Electrical connection, Outlet direction of connection	Cable length [m]	Part no.	Type	
N/O							
	Mounted on the DSM using sensor bracket SL-DSM-B	Contacting	Cable, 3-core, lengthwise	2.5	551365	SME-10M-DS-24V-E-2.5-L-OE	
			Plug M8x1, 3-pin, in-line	0.3	551367	SME-10M-DS-24V-E-0.3-L-M8D	

Proximity switches for size 63

Ordering data – Proximity switch for T-slot, magneto-resistive						Datasheets → Internet: smt
	Type of mounting	Switching output	Electrical connection	Cable length [m]	Part no.	Type
N/O						
	Inserted in the slot from above, flush with the cylinder profile, short design	PNP	Cable, 3-core	2.5	574335	SMT-8M-A-PS-24V-E-2.5-OE
			Plug M8x1, 3-pin	0.3	574334	SMT-8M-A-PS-24V-E-0.3-M8D
			1x M12 plug, 3-pin	0.3	574337	SMT-8M-A-PS-24V-E-0.3-M12
		NPN	Cable, 3-core	2.5	574338	SMT-8M-A-NS-24V-E-2.5-OE
			1x M8 plug, 3-pin	0.3	574339	SMT-8M-A-NS-24V-E-0.3-M8D
N/C						
	Inserted in the slot from above, flush with the cylinder profile, short design	PNP	Cable, 3-core	7.5	574340	SMT-8M-A-PO-24V-E-7.5-OE


Ordering data – Proximity switch for T-slot, magnetic reed							Datasheets → Internet: sme
	Type of mounting	Switching output	Electrical connection	Cable length [m]	Part no.	Type	
N/O							
	Inserted in the slot from above, flush with the cylinder profile	Contacting	Cable, 3-core	2.5	543862	SME-8M-DS-24V-K-2.5-OE	
				5.0	543863	SME-8M-DS-24V-K-5.0-OE	
			Cable, 2-core	2.5	543872	SME-8M-ZS-24V-K-2.5-OE	
			Plug M8x1, 3-pin	0.3	543861	SME-8M-DS-24V-K-0.3-M8D	

Accessories


Inductive proximity sensors for size 12 ... 40

Ordering data – Proximity switches, inductive


Datasheets → Internet: sien

	Thread	Contact	Connection	Part no.	Type
	M5	N/O	Cable, 2.5 m	150370	SIEN-M5B-PS-K-L
			Plug	150371	SIEN-M5B-PS-S-L
	M8	N/O	Cable, 2.5 m	150386	SIEN-M8B-PS-K-L
			Plug	150387	SIEN-M8B-PS-S-L


Connecting cables NEBA, straight, M8 connection

	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M8x1 A-coded to EN 61076-2-104	Open end	3	2.5 m	8078223	NEBA-M8G3-U-2.5-N-LE3
				5 m	8078224	NEBA-M8G3-U-5-N-LE3


Connecting cables NEBA, angled, M8 connection

	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M8x1 A-coded to EN 61076-2-104	Open end	3	2.5 m	8078230	NEBA-M8W3-U-2.5-N-LE3
				5 m	8078231	NEBA-M8W3-U-5-N-LE3

Connecting cables NEBA, straight, M12 connection

	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	Open end	3	2.5 m	8078236	NEBA-M12G5-U-2.5-N-LE3
				5 m	8078237	NEBA-M12G5-U-5-N-LE3

Connecting cables NEBA, angled, M12 connection

	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	Open end	3	2.5 m	8078245	NEBA-M12W5-U-2.5-N-LE3
				5 m	8078246	NEBA-M12W5-U-5-N-LE3

Accessories

Ordering data – One-way flow control valves					Datasheets → Internet: grla	
	For size	Connection Thread	For tubing O.D.	Material	Part no.	Type
For exhaust air						
	12, 16, 25	M5	3	Metal design	193137	GRLA-M5-QS-3-D
			4		193138	GRLA-M5-QS-4-D
			6		193139	GRLA-M5-QS-6-D
	32, 40	G1/8	3		193142	GRLA-1/8-QS-3-D
			4		193143	GRLA-1/8-QS-4-D
			6		193144	GRLA-1/8-QS-6-D
			8		193145	GRLA-1/8-QS-8-D
	63	G1/4	8		193147	GRLA-1/4-QS-8-D
			10		193148	GRLA-1/4-QS-10-D

Ordering data – Centring sleeves for DSM-...-HD					Datasheets → Internet: zbh	
	For size	Description	Part no.	Type	PU ¹⁾	
	12, 16	For centring the drive in the case of side mounting	8146544	ZBH-7-B	10	
	25		8137184	ZBH-9-B		
	32 ... 63		8137185	ZBH-12-B		
	12	For centring attachments on the rotating plate	8146543	ZBH-5-B		
	16 ... 32		8146544	ZBH-7-B		
	40, 63		8137185	ZBH-12-B		
	12, 16	For centring attachments in the middle of the rotating plate	8137185	ZBH-12-B		
	25		191409	ZBH-15		
	40, 63	For centring attachments in the middle of the rotating plate	8023856	ZBH-25	1	
			150901	SLZZ-25/16		

1) Packaging unit